TIANYI SOLAR POWER FLASHLIGHT AND CANDLE LITE
BRING THE LIGHT FOR YOU IN THE NINGHT,
GIVE YOU ONE ROMATIC NIGHT
I CHOOSE,I LIKE

PRODUCT NAME: LED SOLAR POWER FLASHLIGHT
ITEM NO.: TS091
FUNCTION: THE FIRST CHOOSE FOR USING AT HOME, HAVING-CARS,TRAVELLING

LED flashlight and use the basic structure of product Description:

- (1) LED flashlight 3 highlighted the use of LED lights; a Ni-Cd (1.2V A 600mAh) rechargeable battery; high-quality single crystal silicon solar panels constituted
- (2) during the day with direct sun light exposure is to solar panels, solar panels absorb the light energy, into electricity to charge batteries. Will be in charge when the switch button closure.
- (3) charge under the bright light during the day 6 to 8 hours, can be lit for 6 ~ 8 hours.
- (4) When the need to use a flashlight at night, click button power switch, LED light. Do not need to use the other hand, click the button power switch, turn off the power.

BASIC PARAMETERS:
Operating voltage: 1.2V DC
Internal maximum operating voltage: 3.2V
Maximum charge current: 160mA
Maximum operating current: 80mA
Battery capacity: 600mA
Number of charge cycles: 500 times
Open brightness: 2500mcd

PACKING INFORMATION:
Color box size: 16.5X6X6CM
Carton box size:61X34X32CM
100PCS/CTN
G.W.:14.2KGS
N.W:13.2KGS
1X20''Qty: 37,600PCS
1X40''Qty: 75,200PCS
1X40''HQ Qty: 102,400PCS

CE RoHs

CIXI CHINA



Applications:

1,Safe portable night light
2,Window displays
3,Ideal for decor ambiance moon lighting
4,Restaurant/bar/club candle table light
5,Ideal for night party candle lights around garden,pools,decks or patios
6,Good for use party,birthday,church to make harmonious atmosphere!

Product Name: LED Candle Lite
Model No.: TC092

SPECIFICATION:
Opertaing voltage: 3V DC
Internal max. operating voltage: 3V
Max operating current: 20mA
Power supply: 2PCS 1.5V AAA dry batteries
Light time: 50Hours
Operating current:9-20mA

Product Name: Rechargeable LED Candle Lite
Model No.: TC093

SPECIFICATION:
Opertaing voltage: 2.4V DC
Internal max. operating voltage: 2.4V
Max operating current: 20mA
Power supply: 1.2V Ni-Cd batteries inside each Candle Lite are provided to maintain long recharging operations.
Light time: 14Hours
Operating current:9-20mA
Adaptor power requirements: 100-220V AC 50Hz/60Hz 200mA.

Joyous Group (JG)
Address: Room L, 15/F, Block 2, Goldfield Ind. Bldg.,
144-150 Tai Lin Pai Road, Kwai Chung, NT
HONG KONG
Tel: (852) 2401 0382
Fax: (852) 2401 0582
E-mail: cs@joyous.hk
www.joyous.hk